



Vacuum packing machine SV-410T 120/60/1

TABLETOP MODEL. 10 M³/H. 414 MM.

**414 mm. sealing bar.
10 m³/h Busch vacuum pump.**

Deep-drawn chamber.

- Improves the durability of cooked or raw food, with no loss of weight.
- Electronic timer controlling the vacuum process and the sealing of the pack to match the preset time.
- Stainless steel body.
- Stainless steel deep-drawn chamber.
- Cordless sealing bar.
- Softair as standard.
- Digital keyboard.
- LED's indicate each cycle stage whilst performing.
- STOP key allows the interruption of the cycle at any stage, moving on to the next step.
- Pump drying program: improves the durability of the machine.
- Working hours counter display, which allows to know when oil must be replaced.
- NSF-International certified appliance (complying with Hygiene, Cleaning and Food Material regulations).

DEFAULT EQUIPMENT
Insert plate set.

OPTIONAL EQUIPMENT

- Vac-Norm external vacuum kit.
- Bag cutting kit.
- Liquid insert plate set.
- Vacuum sealing bags.

TECHNICAL SPECIFICATIONS

Pump capacity: 10 m³/h
Useful length of the sealing bar: 414 mm
Total Power: 370 W
Vacuum pressure (maximum): 2 mbar

Electrical supply: 120 V / 60 Hz / 1 ~ (6.5 A)
Plug: USA

Internal dimensions

- Width: 430 mm
- Depth: 415 mm
- Height: 145 mm

External dimensions

- Width: 500 mm
- Depth: 500 mm
- Height: 413 mm

Net weight: 64 Kg

AENOR



Empresa Registrada

ER-0437/196



UNE-EN ISO 9001



SAMMIC, S.L.
Basarte, 1 · 20720 AZKOITIA
www.sammic.com

UNE-EN 60335-1:1997, UNE-EN 60335-2-64:2001, EN 55014-1 (2000), EN 55014-2 (1997), EN 61000-3-2 (1995), CNA/CSA C22.2 N°64-M91, UL Std 963

2006/95/EC, 2004/108/EC, NSF/ANSI Standard 169.